



3 pole female TINY xlr cable connector





Article Variations

Article Name	Details	Packaging
RT3FC-B	Black plated housing, gold plated contacts	Plastic Bag
RT3FC-B-D	Black plated housing, gold plated contacts	BULK
RT3FC-B-W	Black plated housing, gold plated contacts, water resistant boot	Plastic Bag
RT3FC-B-W-D	Black plated housing, gold plated contacts, water resistant boot	BULK



Technical Information

Product		
Title	RT3FC-B	
Connection Type	XLR	

Electrical		
Contact Resistance	≤10 mΩ	
Insulation Resistance	>1 GΩ	
Dielectric Strength	>500 V rms	
Rated current per contact	< 5 A	

Mechanical		
Cable O.D. Range	2.0-4.5mm	
Lifetime	>1000 Mating Cycles	
Wiresize	0.22 mm ²	
Wiresize	24 AWG	



Material	
Ground Contact	Steel
Rubber Spring	Rubber
Latch	Zinc
Chuck	POM
Boot	PC/ABS+TPU
Housing	Zinc
Plastic housing	PA6+30%GF
Jack	Bronze
Ground Contact	Bronze
Tube	Aluminum
Latch	Nickel Plating
Housing	Nickel Plating
Jack	Gold Plating
Ground Contact	Tin
Tube	Black Plating