RC5F

5 pole female XLR cable connector

Article Variations

All rights reserved / 12.09.2026

Article Name	Details	Packaging
RC5F	Nickel plated housing, Silver plated contacts	Plastic bag
RC5F-D	Nickel plated housing, Silver plated contacts	BULK
RC5F-B	Black plated housing, gold plated contacts	Plastic bag
RC5F-B-D	Black plated housing, gold plated contacts	BULK
RC5F-BAG	Black plated housing, Silver plated contacts	Plastic bag
RC5F-BAG-D	Black plated housing, Silver plated contacts	BULK

Technical Information

Product	
Title	RC5F
Connection Type	XLR
Gender	female

Electrical	
Contact Resistance	≤ 5 mΩ
Insulation Resistance	> 1.5 GΩ

All rights reserved / 12.09.2026

Mechanical	
Lifetime	>1,000 Mating Cycles
Insertion Force	≤ 30 N
Withdrawal Force	≤ 20 N
Cable O.D.	4 - 7 mm
Wiresize	1.5 mm²
Wiresize	16 AWG

Material	
Plastic Body	PA6+30%GF
Jack	Brass
Ground Contact	Steel
Rubber Ring	Rubber
Button	Zinc
Housing	Zinc
Chuck	POM
Bushing	PA6+30%GF
Push Ring	POM
Boot	PVC
Jack	Sliver Plating
Ground Contact	Tin and Cer
Button	Nickel Plating
Housing	Nickel Plating

All rights reserved / 12.09.2026