

RRX3M-AA-023

3 pole male XLR receptacle, grounding: separate ground contact to mating connector shell and front panel, vertical PCB mount



Features & Benefits

- ✓ Cost effective XLR Chassis solution
- ✓ Gold plated contacts
- ✓ Industrial standard A type panel cut-out & PCB mounting

Technical Information

Product

Title	RRX3M-AA-023
Connection type	XLR
Gender	Male

Electrical

Contact resistance	$\leq 10 \text{ m}\Omega$
Dielectric strength	1.5 kVdc
Insulation resistance	$> 10 \text{ G}\Omega$ (Initial)
Rated voltage	$< 50 \text{ V}$
Grounding Options	Separate ground contact connected to mating connector shell and front panel, no connection to Pin 1

Mechanical

Insertion force	$\leq 40 \text{ N}$
Withdrawal force	$\leq 40 \text{ N}$
Lifetime	> 1000 mating cycles
Wiring	Vertical PCB mount
Locking device	Latch lock
Mounting direction	Rear mounting
Chassis shape	A
Mounting	A-Screw

Material

Contacts	Bronze
Locking element	Steel
Shell	PA

Environmental

Solderability	Complies with IEC 68-2-20
Temperature range	-30 °C to +80 °C
Flammability	UL 94 HB